



BILSTEIN® SHOCK ABSORBERS

**NEW Universal 46mm Motorsports Struts** 

## **BILSTEIN Motorsports Struts feature:**

• Large 46mm linear piston with precise valving profiles

• 50mm OD, hard-chromed strut insert tube for strength

• 14mm piston rod for added side-load support

 Increased oil and nitrogen chamber volume for consistent performance at high operating temperatures

• High-temperature motorsport shock oil

• Durable Viton® wiper seal and inner grease seal

• Schedule 3 olive-drab zinc finish for exceptional corrosion resistance

• 100 micron stainless steel breather vent located at the base of the strut housing

• Four standard valving profiles for each of four travel lengths: 8.8", 7.8", 6.8" and 5.8" stroke

 Threaded spring seat, lock ring and spring hat for use with 2.5" ID to 4" OD barrel springs is included

BILSTEIN's Universal 46mm Motorsport Struts will be available for purchase in Winter 2012.

Part No.	Description
35-212829	8.8" stroke, 380/180 valving
35-212867	8.8" stroke, 300/120 valving
35-212904	8.8" stroke, 300/100 valving
35-214373	8.8" stroke, 180/100 valving
35-212812	7.8" stroke, 380/180 valving
35-212850	7.8" stroke, 300/120 valving
35-212898	7.8" stroke, 300/100 valving
35-214366	7.8" stroke, 180/100 valving
35-212805	6.8" stroke, 380/180 valving
35-212843	6.8" stroke, 300/120 valving
35-212881	6.8" stroke, 300/100 valving
35-214359	6.8" stroke, 180/100 valving
35-212799	5.8" stroke, 380/180 valving
35-212836	5.8" stroke, 300/120 valving
35-212874	5.8" stroke, 300/100 valving
35-214342	5.8" stroke, 180/100 valving

Detailed instructions outlining the critical dimensions as they relate to the components we offer will be available with each kit.

Printed in U.S.A. PP2452 10/12

© 2012 ThyssenKrupp Bilstein of America. All rights reserved.

